Skid Ring Pipe Lubricant

SEAL RING LUBRICANT

TECHNICAL DATA

1.0 DESCRIPTION

Seal Ring Lubricant is specially formulated pipe lubricant for use with concrete pipes having skid ring type joints. It is non-toxic and fully soluble in water.

Light golden.

2.0 PHYSICAL PROPERTIES:

- 2.1 Colour
- 2.2 Specific Gravity
- 2.3 Flashpoint
- 2.4 Viscosity
- 2.5 Toxicity
- D.G. Classification 2.6
- 2.7 Shelf Life
- 2.8 Coverage

09 Non-flammable. Gel like. Non-toxic. Not regulated. 1 year in sealed containers. NA

3.0 USES

Seal Ring Lubricant is used to lubricate the inside of concrete pipes with skid ring type joints. It is non aggressive to rubber and concrete and may be applied by hand. Seal Ring Lubricant may also be used for other applications where a non-toxic, water-soluble lubricant is required (not tested for potable water contact).

4.0 APPLICATION

Apply liberally by hand to the inside of the faucet.

Where chevron rings are used it is advisable to ensure that the area immediately under the ring is well lubricated. This will allow the chevron ring to readily flatten out to its final sealing position.

Precautions should be taken to ensure that rubber rings and contact faces are well cleaned before the lubricant is applied.

After use, the lubricant can be easily removed from hands by washing in warm or cold water.

5.0 PACKAGING

1,2,4 and 20 litres.

Refer to Material Safety Data Sheet for handling and first aid information.



Stratmore Construction Solutions Limited

185 Rata Street | PO Box 35136 | Naenae Lower Hutt 5041 | New Zealand P +64 4 567 8436 | E info@stratmore.co.nz | W stratmore.co.nz

The information contained in this data sheet, is to the best of our knowledge accurate and any recommendations or suggestions which may be made are without liability on our part, since the conditions of use are beyond our control. Users are urged to make their own assessment of our products under their own conditions and for their own requirements. Stratmore Construction Solutions Limited reserves the right to alter formulations without notice. Properties as stated were determined under controlled laboratory conditions. This data sheet may be updated without notice. Please ensure you have the latest copy. If you are a customer, then any contract with you is in accordance with our latest terms and conditions, which are available to download from our website. Where goods are acquired for business purposes, Parts 1 to 4 of the Consumers Guarantee Act 1993 will not apply. To the maximum extent permitted by law, we have no liability (whether statutory, in contract or tor, including negligence) to buyers, users of our products for any physical, direct or indirect damage, economic loss or any other loss or costs caused or contributed by us or any of our agents or employees in respect of any goods or services supplied. Also to the maximum extent permitted by law, all conditions and warranties expressed or implied by statute or common law, equity, trade custom or usage or otherwise howsoever are excluded. If, notwithstanding the foregoing, Stratmore Construction Solutions Limited is from us. Nevertheless limited to the price of the relevant goods or services purchased from us. Page 1 of 1 11