

Complex Formwork Release Agent **TEMCOAT**

TECHNICAL DATA

1.0 DESCRIPTION

TEMCOAT is a combination of refined waxes in an aliphatic solvent. It is designed as a release agent for complex formwork - e.g., skip-tooth band sawn, and for long exposure, where the surface is not to be tiled, plastered or painted. Also suitable as a concrete curing compound not to be subsequently coated or painted.

2.0 PROPERTIES

2.1. Solids Content	7.2%w/v
2.2. Solvent	Aliphatic type Class 3
2.3. Flash Point	36°C
2.4. DG Classification	3
2.5. Coverage	10 – 15m ² per litre depending on surface.

3.0 USES

Use TEMCOAT on wood or steel shutters where surface texture is complex and standard release agents would be unsuitable. Large, skip-tooth band-sawn forms, as used in motorway overpass columns, beams and retaining walls.

Ideal protector for steel and machinery.

Very good curing compound for surfaces that are not to be subsequently coated or treated – bridge beams, columns, etc.

4.0 APPLICATION INSTRUCTIONS

Stir or agitate before use.

Application is preferably by low pressure spray using a solvent-resistant airless sprayer, but roller or brush can be used. Avoid over extension. Apply an even coat to formwork.

Allow TEMCOAT to dry before pouring concrete. On porous surfaces, a second coat may be required. Allow first coat to dry completely (overnight), then apply a second coat. Wipe up or brush-out any puddles or runs. Use only in a well-ventilated area away from ignition sources. Refer to product label before use.

5.0 PRECAUTIONS

Do not use on surfaces that are later to be painted, tiled, hardened, sealed or treated in any manner.

Do not apply when the concrete temperature is less than 5°C. Keep from freezing.

Do not add water, solvent or otherwise dilute the product. TEMCOAT is flammable. Wear protective gloves and clothing when applying. Do not breathe vapours and use only in a well-ventilated area. Refer to safety data sheet for handling and first aid instructions. Read this data sheet in conjunction with product labels.

TEMCOAT

TECHNICAL DATA Continued

6.0 CLEAN UP

Use kerosene or white spirit for equipment. Once dry pre-soak with water miscible type solvent cleaner, or alternatively use Stratmore E-Degreaser. Dissolve TEMCOAT then wash off. Ensure run-off does not enter the environment; dispose of in accordance with local regulations.

7.0 PACKAGING

20-litre pails, 200-litre drums.



**Strat
more.**

Leading solutions for construction.

The information contained in this data sheet, is to the best of our knowledge accurate and any recommendations or suggestions which may be made are without liability on our part, since the conditions of use are beyond our control. Users are urged to make their own assessment of our products under their own conditions and for their own requirements. Stratmore Construction Solutions Limited reserves the right to alter formulations without notice. Properties as stated were determined under controlled laboratory conditions. This data sheet may be updated without notice. Please ensure you have the latest copy. If you are a customer, then any contract with you is in accordance with our latest terms and conditions, which are available to download from our website. Where goods are acquired for business purposes, Parts 1 to 4 of the Consumers Guarantee Act 1993 will not apply. To the maximum extent permitted by law, we have no liability (whether statutory, in contract or tort, including negligence) to buyers, users or specifiers of our products for any physical, direct or indirect damage, economic loss or any other loss or costs caused or contributed by us or any of our agents or employees in respect of any goods or services supplied. Also to the maximum extent permitted by law, all conditions and warranties expressed or implied by statute or common law, equity, trade custom or usage or otherwise howsoever are excluded. If, notwithstanding the foregoing, Stratmore Construction Solutions Limited is found to have any liability, then it is agreed that the liability is nevertheless limited to the price of the relevant goods or services purchased from us.